

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

SECTION 1: IDENTIFICATION

(a) PRODUCT IDENTIFIER: Natural Gas Liquids	(b) SYNONYMS: NGL's, Natural Gas Liquids
--	---

(c) Recommended Use: Blending stock

Restrictions On Use: Not to be used for anything other than recommended use.

(d) Producer:





Chesapeake Energy Corporation and Subsidiaries • 6100 N. Western Avenue, Oklahoma City, OK 73118

Tel: 800-566-9306 • Fax: 405-753-5468

(e) 24 HR EMERGENCY ASSISTANCE PHONE NUMBER: Verisk 3E – 800-451-8346 / Client ID 11906

SECTION 2: HAZARDS IDENTIFICATION

The categories of Health Hazards as defined in OSHA 29 CFR 1910.1200 Hazard Communication Standard have been evaluated and are listed below. Refer to Sections 3, 8, and 11 for additional information.

Hazard Classification	(a) Hazard Category	(b) Hazard Symbols	(b) Signal Word	(b) Hazard Statement	(b) Precautionary Statement
Human Health Hazards					
Acute Toxicity (Oral)	N/D	-	-	-	-
Acute Toxicity (Dermal)	N/D	-	-	-	-
Acute Toxicity (Inhalation)	N/C	-	-	-	-
Skin Corrosion/Irritation	2		Warning	Causes skin irritation	Wear protective gloves P264, P280, P302, P352, P332, P313, P362, P363
Eye Damage/Irritation	2A		Warning	Causes serious eye irritation	Wear eye protection P264, P280, P305, P351, P338, P337, P313
Respiratory Sensitization	-	-	-	-	-
Skin Sensitization	-	-	-	-	-
Germ Cell Mutagenicity	1B		Danger	May cause genetic defects	Wear protective clothing P201, P202, P280, P308, P313, P405, P501
Carcinogenicity	1		Danger	May cause cancer	Do not handle until all safety precautions have been read and understood P201, P202, P280, P308, P313, P405, P501



SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

SECTION 2: HAZARDS IDENTIFICATION

The categories of Health Hazards as defined in OSHA 29 CFR 1910.1200 Hazard Communication Standard have been evaluated and are listed below. Refer to Sections 3, 8, and 11 for additional information.

Hazard Classification	(a) Hazard Category	(b) Hazard Symbols	(b) Signal Word	(b) Hazard Statement	(b) Precautionary Statement
Human Health Hazards					
Reproductive Toxicity	N/D	-	-	-	-
Specific Target Organ Toxicity (STOT) Single-Exposure	3		Warning	May cause drowsiness or dizziness	Avoid breathing vapors P261, P271, P304, P340, P312, P403, P233, P405, P501
Specific Target Organ Toxicity (STOT) Repeated or Prolonged Exposure	N/D	-	-	-	-
Aspiration Hazard	1		Danger	May be fatal if swallowed and enters airways	If swallowed: Immediately call a poison center P301, P310, P331, P405, P501
Simple Asphyxiant	-	-	Warning	May displace oxygen and cause rapid suffocation	-

Health Hazard Precautionary Statement


P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash impacted area thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301+P310	If swallowed: Immediately call a poison center or doctor.
P331	Do not induce vomiting.
P302+P352	If on skin: Wash with plenty of water and soap.
P312	Call a poison center or doctor if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P363	Take off contaminated clothing. Wash contaminated clothing before reuse.
P304+P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P308+P313	If exposed or concerned. Get medical advice/attention.
P403	Store in a well-ventilated place.
P405	Store locked up.

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

Health Hazard Precautionary Statement	
P501	Dispose of contents/container to approved disposal facility.


Hazard Classification	Hazard Category	Hazard Symbols	Signal Word	Hazard Statement	Precautionary Statement
Physical Hazards					
Explosives	N/C	-	-	-	-
Flammable Gases	N/C	-	-	-	-
Flammable Aerosols	N/C	-	-	-	-
Oxidizing Gases	N/C	-	-	-	-
Gases Under Pressure	N/C	-	-	-	-
Flammable Liquids	1		Danger	Extremely flammable liquid and vapor	Keep away from heat/sparks/open flames/hot surfaces. No Smoking P210, P233, P235, P240, P241, P242, P243, P280, P303, P361, P353, P370, P378, P403, P501
Flammable Solids	N/C	-	-	-	-
Self-reactive Substances and Mixtures	N/C	-	-	-	-
Substances and mixtures which react with water to emit flammable gases	N/C	-	-	-	-
Oxidizing Liquids	N/C	-	-	-	-
Oxidizing Solids	N/C	-	-	-	-
Organic Peroxides	N/C	-	-	-	-
Corrosive to Metals	N/C	-	-	-	-

Physical Hazard Precautionary Statement	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P235	Keep cool.
P240	Ground/Bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.

SAFETY DATA SHEET

Natural Gas Liquids
Version 1.2 Revision Date: 9/26/2019

P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/eye protection/face protection.
P303+P61+P353	If on skin or hair: Remove/take off immediately all contaminated clothing. Rinse skin with water/shower
P370+P378	In case of fire. Use dry chemical, carbon dioxide, or foam for extinction.
P403	Store in a well-ventilated place.
P501	Dispose of contents/container to an approved disposal facility.

Hazard Classification	(a) Hazard Category	(b) Hazard Symbols	(b) Signal Word	(b) Hazard Statement	(b) Precautionary Statement
Environmental Hazards					
Acute Toxicity to the Aquatic Environment	2	-	-	Toxic to aquatic life	-
Chronic Toxicity to the Aquatic Environment	2		-	Toxic to aquatic life with long lasting effects	-

(c) Hazards not otherwise classified: This material may contain or release poisonous hydrogen sulfide. In high doses, hydrogen sulfide may produce pulmonary edema and respiratory depression or paralysis. Exposure to hydrocarbon can sensitize the myocardium to epinephrine-induced cardiac arrhythmias. If vapors are released via product heating, all efforts should be made to adequately characterize the air quality within the environment to ensure exposure below relevant occupational exposure levels.

(d) Unknown acute toxicity: None Identified.

Medical conditions which are generally recognized as being aggravated by exposure: Populations with chronic respiratory, skin, or eye disease are at increased risk from exposure.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS				
Hydrocarbon Ranges	(a) Chemical name (b) (Common name and synonyms)	(c) CAS No.	(c) EC No.	(b) % Weight
	Natural Gas (petroleum), raw liquid mix ¹	64741-48-6	265-048-9	100%
Components				
C ₁ – C ₃	Asphyxiant gases (methane, ethane, propane)	-	-	4 – 9
C ₄	Butane (all isomers)	-	-	15 – 22
C ₅	Pentanes	-	-	23 – 26
C ₆ – C ₈	“Light aliphatic” (C ₇ – C ₉ aliphatic hydrocarbons; heptane)	-	-	27 – 33
	n-Hexane	110-54-3	203-777-6	6 – 10
C ₉ – C ₁₈	“Mid-range aliphatic” (C _{>8} -C ₁₆ aliphatic hydrocarbons)	-	-	1 – 4
C ₆	Benzene	71-43-2	200-753-7	0.1 – 0.5
	Hydrogen sulfide	7783-06-4	231-977-3	< 0.5 highly variable

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

¹A complex combination of hydrocarbons separated as a liquid from natural gas in a gas recycling plant by processes such as refrigeration or absorption. It consists mainly of saturated aliphatic hydrocarbons having carbon numbers in the range C₂ through C₈. The concentration ranges listed above are based on specific testing results and reported industry values. Components of this product are normally within the ranges listed above; however, depending on the geographical source, gas composition may vary.

SECTION 4: FIRST AID MEASURES

(a) Description of necessary measures:

Emergency Medical advice is available from

INHALATION:	Move to fresh air immediately. If breathing stops, provide artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
INGESTION:	Rinse mouth and drink plenty of water or milk. There is a potential for aspiration if swallowed. Do not induce vomiting. If vomiting occurs, place on left side and keep head low. Seek medical help immediately.
SKIN CONTACT:	Remove contaminated clothing immediately. Wash affected areas with soap and water. If skin irritation occurs, call a physician.
EYE CONTACT:	Flush eyes immediately with water for 15 minutes while holding eyelids open. If irritation persists seek medical attention.

(b) Most important symptoms/effects:

- **Acute:** Headache, drowsiness, loss of mental alertness and coordination, dizziness, nausea.
- **Delayed:** Dry skin and possible irritation with repeated or prolonged exposure.

(c) Indication of immediate medical attention and special treatment: Significant over-exposure

Notes to physician: Treat symptomatically and supportively.

General advice: In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Show this safety data sheet to the doctor in attendance. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

SECTION 5: FIRE FIGHTING MEASURES

(a) Suitable extinguishing media: Dry chemical, carbon dioxide, water spray or alcohol resistant foam.

Unsuitable extinguishing media: High volume water jet. It will spread the fire.

(b) Specific hazards arising from the chemical: Natural gas liquids are extremely flammable. It can be ignited by heat, spark, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, and pagers which have not been certified as intrinsically safe). Vapors can travel considerable distances to spaces, outdoors, or in sewers. This product will float and can be reignited on surface water. Vapors are heavier than air and can accumulate in low-lying areas. If container is not properly cooled, it can rupture in the heat of a fire. Hazardous combustion/decomposition products may be released by this material when exposed to heat or fire. Use caution and wear appropriate PPE, including respiratory protection and flame retardant clothing.

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

(c) Special protective equipment and precautions for fire-fighters: Shut off flow immediately if it can be done safely. Isolate the area from personnel. Keep personnel upwind from fire. Fire fighters should use appropriate self-contained breathing apparatus (SCBA) while in close proximity to fire and vapors coming from product. Move personnel upwind of any smoke or vapors.

In the event of fire and/or explosion, do not breathe fumes.

(d) Flammability/Explosivity: NFPA RATING 704 Hazard Class:
Health = 1 (=3 if hydrogen sulfide is present)
Fire = 4
Instability = 0
(0-Minimal, 1-Slight, 2-Moderate, 3-Serious, 4-Severe)

(e) Hazardous Decomposition Products: Normal combustion forms carbon dioxide and water vapor; incomplete combustion may produce carbon monoxide.

SECTION 6: ACCIDENTAL RELEASE MEASURES

(a) Personal precautions, Protective equipment, and Emergency procedures: Natural gas liquid is extremely flammable. Stay upwind if possible. Eliminate all ignition sources. Avoid inhalation of vapors and spray mist. Avoid contact with skin and eyes. Wear appropriate PPE including respiratory protection as needed.

(b) Methods and materials for containment and cleaning up: Remove sources of ignition. Beware of explosion danger. Stop flow of product, if it is safe to do so. Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended if possible. Dike the spilled material. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water, remove with appropriate methods (e.g., skimming, booms, or absorbent boom). In the case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spill scenarios for this material; however, local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

Environmental Precautions: Prevent product from entering drains and sanitary sewers. Prevent further leakage or spillage if safe to do so. If product impacts rivers, lakes, drains, or any other body of water, contact appropriate authorities.

SECTION 7: HANDLING AND STORAGE

(a) Precautions for safe handling: Keep away from ignition sources such as heat/sparks/open flame. Take precautionary measures against static discharge. Non-sparking tools should be used. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not eat, drink, or smoke when using this product. Do not breathe vapors or mists. Use only outdoors or in well-ventilated area. Wear protective gloves/clothing and eye/face protection. Wash thoroughly after handling. Use good personal hygiene practices and wear appropriate personal protective equipment including flame retardant clothing.

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

Natural gas liquids are extremely flammable. It may vaporize easily at ambient temperatures. The vapor is heavier than air and may create an explosive mixture of vapor and air. Beware of accumulation in confined spaces and low-lying areas. Open container slowly to relieve any pressure. Electrostatic charge may accumulate and create a hazardous condition when handling or processing this material. To avoid fire or explosion, dissipate static-electricity during transfer by grounding and bonding containers and equipment before transferring material. The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes). Refer to NFPA-70 and/or API RP 2003 for specific bonding/grounding requirements. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames. Avoid vapors when opening tank hatches and dome covers.

Static Accumulation Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding of tanks, transfer piping, and storage tank level floats are necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. Special care should be given to ensure that slow load procedures for “switch loading” are followed to avoid the static ignition hazard that can exist when higher flash point material is loaded into tanks previously containing low flash point products. For more information, refer to OSHA Standard 29 CFR 1910.106 ‘Flammable and Combustible Liquids’, National Fire Protection Association (NFPA 77, ‘Recommended Practice on Static Electricity’, and/or the American Petroleum Institute (API) Recommended Practice 2003, ‘Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents’.

(b) Conditions for safe storage, including any incompatibilities: Check atmosphere for oxygen content, and flammability prior to entry. Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (See Section 10). Protect containers against physical damage. Outdoor and detached storage is preferred. Indoor storage should meet OSHA standards and appropriate fire codes. “Empty” containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. “Empty” drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum re-conditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1, and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:			
Components	(a) OSHA PEL ¹	(a) ACGIH TLV ²	(a) IDLH ³
Propane	1,000 ppm (TWA)	NE	2,100 ppm
Butane (all isomers)	NE	1,000 ppm (C)	NE

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

Pentane (all isomers)	1,000 ppm (TWA)	1,000 ppm (TWA)	1,500 ppm
“Light aliphatic”	NE	NE	NE
n-Hexane	500 ppm (TWA)	50 ppm (TWA) Skin	1,100 ppm
“Mid-range aliphatic”	NE	NE	NE
Benzene	1 ppm (TWA) 5 ppm (STEL)	0.5 ppm (TWA) 2.5 ppm (STEL) Skin	500 ppm
Hydrogen sulfide	20 ppm (C)	1 ppm (TWA) 5 ppm (STEL)	100 ppm

Notes:

1. OSHA PEL are 8-hour TWA (Time-weighted average) concentrations unless otherwise noted. A (“C”) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday.
2. Threshold Limit Values – TWA established by the ACGIH represents the TWA concentration for a conventional 8-hour workday and a 40-hour workweek, to which it is believed that nearly all workers may be repeatedly exposed, day after day, for a working lifetime without adverse effect; Short-Term Exposure Limit (TLV-STEL) represents a 15-minute TWA exposure that should not be exceeded at any time during a work day. ACGIH TLV’s are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.
3. The “immediately dangerous to life or health air concentration values (IDLHs)” are used by NIOSH as part of a respiratory selection criteria.
4. No exposure limits have been developed by the producer.

(b) Appropriate engineering controls: Provide adequate general and local ventilation to maintain airborne chemical concentrations below applicable exposure limits, to prevent accumulation of flammable vapors and formation of explosive atmosphere, and to prevent formation of an oxygen deficient environment. Use non-sparking explosion proof, totally enclosed ventilation systems. Only use non-sparking tools, if engineering controls or work activities are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Eye/face protection: Wear approved safety glasses/goggles with side shields and/or an appropriate full-face shield. All eye protection should be selected and worn in accordance with the OSHA eye and face protection guidelines outlined in 29 CFR 1910.132 and 1910.133.

Skin Protection: Wear appropriate clothing to prevent skin contact. Thoroughly decontaminate any articles of clothing that come into contact with product. The use of gloves is advised to prevent skin exposure and contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and conditions, additional protection may be necessary to prevent skin contact including items such as chemical resistant boots, aprons, arm covers, hoods, coveralls, or encapsulated suits. All PPE should be selected and worn in accordance with 29 CFR 1910.132 and 1910.138.

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

Respiratory protection: A positive pressure air line with full-face mask and escape bottle or a self-contained breathing apparatus (SCBA) should be available in case of an emergency and cases when the TLV is exceeded. All respirators should be selected and worn in accordance with 29 CFR 1910.132 and 1910.134.

General hygiene considerations: Always observe good personal hygiene measures, such as washing after handling the material, and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

General: Wear chemical protective equipment. Launder contaminated clothing before reuse.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties	
	Solution:
(a) Appearance:	Clear, colorless liquid
(b) Odor:	Gasoline-like
(c) Odor Threshold:	N/A
(d) pH:	N/A
(e) Melting point/Freezing point:	N/A
(f) Boiling point/range:	23 - 28 °C
(g) Flash Point:	< -100 °F / -38 °C
(h) Evaporation rate:	N/A
(i) Flammability:	N/A
(j) UFL/LFL or UEL/LEL:	N/A
(k) Vapor pressure:	14-7, 150 mm Hg at 25 °C
(l) Vapor density:	>1
(m) Relative density:	N/A
(n) Solubility:	Negligible
(o) Partition coefficient:	N/A
(p) Auto-ignition temperature:	N/A
(q) Decomposition temperature:	N/A
(r) Viscosity:	N/A
(s) Specific Gravity:	0.5-0.8

SECTION 10: STABILITY AND REACTIVITY

(a) Reactivity: Saturated aliphatic hydrocarbons, which are contained in natural gas liquids, may be incompatible with strong oxidizing agents like nitric acid. Charring of the hydrocarbon may occur followed by ignition of unreacted hydrocarbon and other nearby combustibles. In other settings, aliphatic saturated hydrocarbons are mostly unreactive. They are not affected by aqueous solutions of acids, alkalis, most oxidizing agents, and most reducing agents. When heated sufficiently or when ignited in the presence of air, oxygen or strong oxidizing agents, they burn exothermically to produce carbon dioxide and water. May be ignited by strong oxidizers.

(b) Chemical stability: Material is stable under normal conditions.

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

- (c) **Possibility of hazardous reactions:** Hazardous polymerization will not occur.
- (d) **Conditions to avoid (e.g., static discharge, shock, or vibration):** Excess heat, incompatible materials.
- (e) **Incompatible materials:** Strong acids, Strong oxidizing agents.
- (f) **Hazardous decomposition products:** carbon dioxide, carbon monoxide.
- (g) **Hazardous Polymerization:** N/A

SECTION 11: TOXICOLOGICAL INFORMATION

(a) Information on likely routes of exposure:

- **Inhalation:** causes irritation of upper respiratory tract; central nervous system stimulation followed by depression of varying degrees ranging from dizziness, headache, and incoordination to anesthesia, coma, and respiratory arrest; irregular heartbeat is dangerous complication.
- **Accidental Ingestion:** causes irritation of mucous membranes of throat, esophagus, and stomach; stimulation followed by depression of central nervous system; irregular heartbeat.
- **Skin contact:** May cause skin irritation.
- **Eye contact:** May cause minimal to moderate irritation.

(b) **Symptoms related to physical, chemical and toxicological characteristics:** Skin contact may cause dermal irritation.

(c) **Delayed and immediate effects and also chronic effects from short- and long-term exposure:** Chronic skin exposures can lead to dermatitis.

(d) Numerical measures of toxicity:

Acute Toxicity (Oral)			
Chemical	Tested % Weight	Model	LD ₅₀ Range (mg/kg bw)
C ₁ – C ₃			No data available
n-Butane			No data available
Pentanes	100	Rat	> 2,000 mg/kg
n-Hexane	100	Mouse	5,000 mg/kg
C ₆ -C ₈ Aliphatic Hydrocarbons (minus n-hexane)	100	Rat	>5,000 - > 15,000 mg/kg
C _{>8} -C ₁₆ Aliphatic Hydrocarbons	100	Mouse	>5,000 – 15,800 mg/kg
Benzene	100	Rat	3,306 mg/kg
Hydrogen Sulfide	70%	Rat	100 -215 mg/kg

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

Acute Toxicity (Dermal)			
Chemical	% Weight	Model	LD ₅₀ Range (mg/kg bw)
C₁ – C₃		No data available	
Butane		No data available	
Pentanes	100	Rabbit	3,000 mg/kg
n-Hexane	100	Rabbit	3,000 mg/kg
C₆-C₈ Aliphatic Hydrocarbons (minus n-hexane)	100	Rabbit	> 2,920 - > 3,160 mg/kg
C_{>8}-C₁₆ Aliphatic Hydrocarbons	100	Rabbits & rats	> 2,000 mg/kg
Benzene	100	Rabbit	8,260 mg/kg
Hydrogen sulfide			No data available

Acute Toxicity (Inhalation)			
Chemical	Model	LD ₅₀ Range (mg/L)	
C₁ – C₃	Rat	>1,464 mg/L/15 min	
n-Butane	Rat	658 mg/L	
Pentanes	Rat	> 18 mg/L	
n-Hexane	Rat	169 mg/L	
C₆-C₈ Aliphatic Hydrocarbons (minus n-hexane)	Rat	> 23 to > 33 mg/L	
C_{>8}-C₁₆ Aliphatic Hydrocarbons	Rat	24 mg/L	
Benzene	Rat	31.9 mg/L	
Hydrogen Sulfide	Rat	380 – 1,500 mg/m ³	

Skin Damage and/or Irritation:

Prolonged skin contact may cause mild to moderate irritation

Eye Damage and/or Irritation:

Direct contact with the eyes may cause minimal to moderate eye irritation

Respiratory Sensitization:

No data available

Skin sensitization:

No evidence available

Germ Cell Mutagenicity:

Some components (benzene) may cause chromosomal aberrations

Reproductive Toxicity:

Some evidence of reproductive toxicity for some components (C1-C3 hydrocarbons, n-hexane, hydrogen sulfide)

Specific Target Organ Toxicity (Single Exposure):

Not classified; some evidence of CNS effects, e.g. drowsiness and dizziness

Specific Target Organ Toxicity (Repeated Exposure):

May cause effects on the central nervous system, hematological system, liver and kidney through prolonged or repeated exposures

Aspiration Hazard:

May cause pneumonitis upon swallowing as aspiration into the lung is possible. May be fatal.

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

(e) Carcinogenicity:

Carcinogenicity				
Compound	ACGIH	IARC	NTP	OSHA
C₁ – C₃	Not classified	Not classified	Not listed	Not classified
Butane	Not classified	Not classified	Not listed	Not classified
Pentanes	Not classified	Not classified	Not listed	Not classified
n-Hexane	Not classified	Not classified	Not listed	Not classified
C₆-C₈ Aliphatic Hydrocarbons (minus n-hexane)	Not classified	Not classified	Not listed	Not classified
C₈-C₁₆ Aliphatic Hydrocarbons	Not classified	Not classified	Not listed	Not classified
Benzene	A1 – Confirmed Human Carcinogen	Group 1 – Carcinogenic to Humans	Known to be a human carcinogen	Carcinogen
Hydrogen sulfide	Not classified	Not classified	Not listed	Not classified

SECTION 12: ECOLOGICAL INFORMATION

(a) Ecotoxicity: This material is expected to be potentially toxic to aquatic organisms. Ecotoxicity data have not been determined specifically for this mixture. A range of measurements of aquatic toxicity has been obtained in laboratory studies of hydrocarbon mixtures with LC₅₀ or EC₅₀ values in the range of 1 to 100 mg/L. The values are generally consistent with the predicted aquatic toxicity of this mixture based on the hydrocarbon composition. Acute toxicity could potentially fall within the range of 1 – 10 mg/L, depending on the proportion of low molecular weight hydrocarbons in the mixtures composition (EPA, 2011).

(b) Persistence and degradability: Hydrocarbon mixtures are not considered readily biodegradable and most nonvolatile components are not biodegradable. Some components are persistent in water. Lighter components will tend to evaporate but the heavier components may become dispersed in water or absorbed to soil or sediment.

(c) Bioaccumulative potential: The octanol water coefficient (Log K_{ow}) values for the hydrocarbon components of this material range from less than 2 to greater than 6, and therefore would be regarded as having the potential to bioaccumulate.

(d) Mobility in soil: Some components may be mobile and contaminate groundwater.

(e) Other adverse effects: Coating with this mixture can kill birds, plankton, aquatic life, algae, and fish.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations. Dispose of waste in accordance with the federal, state, and local laws and regulations. This material is listed as a RCRA hazardous waste under 40 CFR 261-271. The product can be an ignitable hazardous waste.

SAFETY DATA SHEET

Natural Gas Liquids**Version 1.2 Revision Date: 9/26/2019**

Containers should be completely used and emptied prior to discarding. Residues from containers can possibly be considered to be hazardous wastes.

EPA Waste Number:

D001-Ignitability Characteristic

DO18-Toxicity Characteristic (Benzene)

SECTION 14: TRANSPORT INFORMATION**Special Precaution for user: Read safety instructions, SDS, and emergency procedures before handling.****UN Number: UN 1075**

SHIPPING NAME:	Liquefied Petroleum Gas	IATA HAZARD CLASS:	2.1
DOT HAZARD CLASS:	2.1	IMDG CLASS:	2.1
PLACARD:	Flammable Gas/1075	ADR/ERG CODES:	
PACKING GROUP:	NA	PACKING GROUP:	
LABEL:	Flammable Gas	ADR HAZARD CLASS:	

Emergency Response Guide: 115**U.S. Department of Transportation (DOT)****Shipping Description:** If vapor pressure is > 300 kPa (43.5 psia) at 50° C (122° F) shipping description is:

UN1965, Hydrocarbon gas mixture, liquefied, n.o.s., 2.1. If vapor pressure is <= 300 kPa (43.5 psia) at 50° C (122° F) shipping description is: UN3295, Hydrocarbons, liquid, n.o.s., 3, I or II [I if BP < 95° F (35° C); II if BP > 95° F]

Non-Bulk Package Marking: Must be consistent with shipping description, either:

Hydrocarbon gas mixture, liquefied, n.o.s., UN1965 or Hydrocarbons, liquid, n.o.s., UN3295

Non-Bulk Package Labeling: For UN1965: Flammable gas; For UN3295: Flammable liquid**Bulk Package/Placard Marking:** For UN1965: Flammable gas / 1965; For UN3295: Flammable / 3295**Packaging - References:** For UN1965: 49 CFR: 173.306; 173.304; 173.314 & .315; For UN3295: 49 CFR 173.150; 173.201; 173.243 [PG I] -or- 49 CFR 173.150; 173.202; 173.242 [PG II] (Exceptions; Non-bulk; Bulk)**Hazardous Substance:** See Section 15 for RQ's**Emergency Response Guide:** UN1965 - 115; UN3295 - 128;

Other shipping description elements may be required for DOT compliance.

SECTION 15: REGULATORY INFORMATION

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

CERCLA/SARA-Section 311/312 (Title III Hazard Categories)

Acute Health	Yes
Chronic Health	Yes
Fire Hazard	Yes

SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

Pressure Hazard Yes
 Reactive Hazard No

US EPCRA (SARA Title III) Section 313-Toxic Chemical: De minimis concentration

Component	de minimis
Benzene	0.1%
n-Hexane	1.0%

CERCLA (Superfund) reportable quantity (lbs.)

EPA's Petroleum Exclusion applies to this material - (CERCLA 101(14))

CERCLA (Superfund) reportable quantity (lbs.)

California Proposition 65: Warning: This material may contain detectable quantities of the following chemicals, known to the State of California to cause cancer, birth defects or other reproductive harm, and which may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5): benzene and n-hexane.

Component Analysis - State

Component	CAS	CA	MA	MN	NJ	PA	RI
Benzene	71-43-2	Yes	Yes	Yes	Yes	Yes	Yes
n-Hexane	110-54-3	Yes	Yes	Yes	Yes	Yes	Yes

National Chemical Inventories:

All components are either listed on the US TSCA Inventory or are not regulated under TSCA.
 All components are either on the DSL or are exempt from DSL listing requirements.

Canadian WHMIS Classification:

- Class A: Compressed gas
- Class B-1: Flammable gas
- Class D2A: Material causing other toxic effects (Very toxic)
- Class D2B: Material causing other toxic effects (Toxic)

U.S. Export Control Classification Number: EAR99

SECTION 16: OTHER INFORMATION

This Safety Data Sheet is authored pursuant to the OSHA Hazard Communication/HazCom 2012 Final Rule.

COMMON TERMS AND ACRONYMS:

- ACGIH:** American Conference of Governmental Industrial Hygienists
- C:** Ceiling Limit
- CAS#:** Chemical Abstracts System Number
- CERCLA:** Comprehensive Environmental Response, Compensation, and Liability Act
- CNS:** Central Nervous System

SAFETY DATA SHEET

Natural Gas Liquids**Version 1.2 Revision Date: 9/26/2019**

DOT:	Department of Transportation
DSL:	Domestic Substance List
EC₅₀:	Effective concentration that inhibits the endpoint to 50% of control population
EINECS:	European List of Notified Chemical Substances
EPA:	U.S. Environmental Protection Agency
ESIS:	European Chemical Substances Information System
HMIS:	Hazardous Materials Identification System
IARC:	International Agency for Research on Cancer
IDLH:	Immediately Dangerous to Life and Health
IATA:	International Air Transport Association
IMDG:	International Maritime Dangerous Goods
LC₅₀:	Concentration of air resulting in death to 50% of experimental animals
LD₅₀:	Administered dose resulting in death to 50% of experimental animals
LEL:	Lower Explosive Limit
MSHA:	Mine Safety and Health Administration
NFPA:	National Fire Protection Association
NIOSH:	National Institute for Occupational Safety and Health
N/A:	Not Available
N/C:	Not Classified
N/D:	No applicable data available
NE:	Not Established
NOAEC:	No Observed Adverse Effect Concentration
NTP:	National Toxicology Program
OECD:	Organisation for Economic Co-operation and Development
OSHA:	Occupational Safety and Health Administration
PEL:	Permissible Exposure Limit
PPE :	Personal Protective Equipment
RCRA:	Resource Conservation and Recovery Act
SARA:	Superfund Amendments and Reauthorization Act
SCBA:	Self-Contained Breathing Apparatus
STEL:	Short Term Exposure Limit
STP:	Standard Temperature and Pressure
TLV:	Threshold Limit Value
TSCA:	Toxic Substances Control Act
TWA:	Time Weighted Average
UEL:	Upper Explosive Limit
WHMIS:	Workplace Hazardous Materials Information System

Disclaimer:

The information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief, but it is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgement.



SAFETY DATA SHEET

Natural Gas Liquids

Version 1.2 Revision Date: 9/26/2019

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in their use of the material.

Date of SDS Revisions: Version 1.2 – 9/26/2019 (HSER)
 Version 1.1 – 5/24/2019 (EHS&R)
Date of SDS Preparation: 5/26/2015
SDS Prepared by: Center for Toxicology and Environmental Health, LLC.